

Rodamiento de bolas 2208-E-2RS1-TN9-C3-SKF

2208-E-2RS1-TN9-C3-SKF

LE BON ROULEMENT

| Principal dimensions | | Basic load ratings | | Fatigue load limit | Speed ratings | | Mass | Designations | | |
|----------------------|----|--------------------|------|--------------------|----------------|-----------------|----------------|--------------|-------------------------------|---------------------------|
| d | D | B | C | C ₁₀ | P ₀ | Reference speed | Limiting speed | kg | Bearing with cylindrical bore | Bearing with tapered bore |
| mm | | | mm | | mm | min | max | | | |
| 40 | 80 | 22 | 33,9 | 10 | 0,52 | 36 000 | 12 000 | 0,32 | 2208 ETN9 | 2208 EKTN9 |

| Overlays | | | | Abutment and fillet dimensions | | | Calculation factors | | | | |
|----------|----------------|----------------|-----------------------|--------------------------------|---------------------|---------------------|---------------------|------|----------------|----------------|----------------|
| d | d ₁ | D ₁ | r _{1,2} min. | r _a min. | D _a max. | r _a max. | k _a | e | Y ₁ | Y ₂ | Y ₃ |
| mm | | | | mm | | | | | | | |
| 40 | 50,4 | 71,4 | 1,1 | 47 | 72 | 3,1 | 0,046 | 0,28 | 2,2 | 3,5 | 2,5 |



Rodamiento de bolas 2208-E-2RS1-TN9-C3-SKF

| Caractéristique | Valeur |
|----------------------------|--|
| d - Diámetro interior (mm) | 40 |
| D - Diámetro exterior (mm) | 80 |
| C - Espesor (mm) | 23 |
| Marca | SKF |
| Tipo del rodamiento | De bolas |
| Juego | Alta velocidad (C3, J30) |
| Tipo de sellado | Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE) |
| Tipo de jaula | Poliamido |
| Agujero | Cilíndrico/a |
| Rodamiento serie | 2200 |
| Unidad de venta | pieza |

