

Rodamiento de bolas 2308-EM-P6-SKF

2308-EM-P6-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designations			
d	D	B	C	C ₁₀	P ₀	Reference speed	Limiting speed	kg	Bearing with cylindrical bore		tapered bore
mm			mm	mm	mm	min	min		2308 ETN9		2308 DETH9
40	90	22	14	14	0,82	14 000	10 000	0,93			

Dimensions				Abutment and fillet dimensions			Calculation factors				
d	d ₂	D ₁	r _{1,2} min.	r _a min.	D _a max.	r _s max.	k	e	Y ₁	Y ₂	Y ₃
mm				mm							
40	53,7	76,2	1,5	4,9	81	1,5	0,05	0,4	1,6	2,4	1,6



Rodamiento de bolas 2308-EM-P6-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	40
D - Diámetro exterior (mm)	90
C - Espesor (mm)	33
Marca	SKF
Tipo del rodamiento	De bolas
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Macisa latón
Agujero	Cilíndrico/a
Especificaciones	Clase de precisión P6
Rodamiento serie	2300
Unidad de venta	pieza

