

Rodamiento de bolas 619/4

619/4





| Dimensions (mm)<br>Dimension (mm) |           |           | Coefficient de charge (90%)<br>Load rating (kN) |                            | Vitesse limite (1/min)<br>Speed limit (Rpm) |              | Poids (kg)<br>Weight (Lb) | Sigle<br>Designation |
|-----------------------------------|-----------|-----------|-------------------------------------------------|----------------------------|---------------------------------------------|--------------|---------------------------|----------------------|
| d<br>(mm)                         | D<br>(mm) | B<br>(mm) | Dynamique<br>C                                  | Statique<br>C <sub>0</sub> | Lubrification<br>Lubrication                |              |                           |                      |
|                                   |           |           |                                                 |                            | Grasse<br>Grease                            | Huile<br>Oil |                           |                      |
| 8                                 | 11        | 4         | 0.303                                           | 0.220                      | 21200                                       | 70000        | 0.0019                    | 619/4                |



**Rodamiento de bolas 619/4**

| Caractéristique            | Valeur                |
|----------------------------|-----------------------|
| d - Diámetro interior (mm) | 4                     |
| D - Diámetro exterior (mm) | 11                    |
| C - Espesor (mm)           | 4                     |
| Marca                      | Genérica alta calidad |
| Tipo del rodamiento        | De bolas              |
| Juego                      | Estándar              |
| Tipo de sellado            | No estanco            |
| Tipo de jaula              | Acero                 |
| Rodamiento serie           | 610                   |
| Unidad de venta            | pieza                 |

