

Rodamiento de bolas S625-2RS-ZEN

S625-2RS-ZEN



LE BON

ROULEMENT



| Dimension (mm)         |     |      |     | Designation/Type |           |              |           |              |           |
|------------------------|-----|------|-----|------------------|-----------|--------------|-----------|--------------|-----------|
| standard               | d   | D    | B   | open             |           | ZZ           |           | 2RS/215      |           |
| or flanged<br>standard | 6.0 | 18.0 | 5.0 | Chrome Steel     | Stainless | Chrome Steel | Stainless | Chrome Steel | Stainless |
|                        |     |      |     | 625              | 625       | 625-02       | 625-02    | 625-2RS      | 625-2RS   |

| * Load Rating (only ISO C4) |            | * Limiting Speed x1000 rpm<br>(open & ZZ) |      | Standard<br>cage type<br>(Grease or oil) | Weight (g) approx. |
|-----------------------------|------------|-------------------------------------------|------|------------------------------------------|--------------------|
| C, dyn. N                   | C, stat. N | Grease                                    | Oil  | WJ                                       | < 6 g              |
| 1720                        | 675        | 30.0                                      | 40.0 |                                          |                    |



**Rodamiento de bolas S625-2RS-ZEN**

| Caractéristique            | Valeur                                           |
|----------------------------|--------------------------------------------------|
| d - Diámetro interior (mm) | 5                                                |
| D - Diámetro exterior (mm) | 16                                               |
| C - Espesor (mm)           | 5                                                |
| Marca                      | ZEN                                              |
| Tipo del rodamiento        | De bolas                                         |
| Juego                      | Estándar                                         |
| Tipo de sellado            | Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE) |
| Tipo de jaula              | Acero                                            |
| Especificaciones           | Acero inoxidable                                 |
| Rodamiento serie           | 620                                              |
| Unidad de venta            | pieza                                            |

