


Rodamiento de bolas S692-X-ZEN

S692-X-ZEN





|            | Dimension (mm) |     |     | Designation/Type |           |              |           |              |           |
|------------|----------------|-----|-----|------------------|-----------|--------------|-----------|--------------|-----------|
| standard   | d              | D   | B   | open             |           | ZZ           |           | 2RS/2IS      |           |
| or flanged |                |     |     | Chrome Steel     | Stainless | Chrome Steel | Stainless | Chrome Steel | Stainless |
| standard   | 2.5            | 7.0 | 2.9 | 692X             | S692X     |              |           |              |           |

| * Load Rating (only 180 CR) |            | * Limiting Speed x1000 rev (open & ZZ) |      | Standard cage type (Grease or oil) | Weight (g) approx. |
|-----------------------------|------------|----------------------------------------|------|------------------------------------|--------------------|
| C, dyn. N                   | C, stat. N | Grease                                 | Oil  | W                                  | + 1 g              |
| 368                         | 128        | 60.0                                   | 75.0 |                                    |                    |



**Rodamiento de bolas S692-X-ZEN**

| Caractéristique            | Valeur           |
|----------------------------|------------------|
| d - Diámetro interior (mm) | 2,5              |
| D - Diámetro exterior (mm) | 7                |
| C - Espesor (mm)           | 2,5              |
| Marca                      | ZEN              |
| Tipo del rodamiento        | De bolas         |
| Juego                      | Estándar         |
| Tipo de sellado            | No estanco       |
| Tipo de jaula              | Acero            |
| Especificaciones           | Acero inoxidable |
| Rodamiento serie           | 690              |
| Unidad de venta            | pieza            |

