

Rodamiento de bolas S61916-2RS-ZEN

S61916-2RS-ZEN





| Dimension (mm) |      |       |      | Designation/Type |           |              |           |              |            |
|----------------|------|-------|------|------------------|-----------|--------------|-----------|--------------|------------|
|                | d    | D     | B    | name             |           | S2           |           | SRS/2TS      |            |
| standard       |      |       |      | Chrome Steel     | Stainless | Chrome Steel | Stainless | Chrome Steel | Stainless  |
| or flanged     |      |       |      |                  |           |              |           |              |            |
| standard       | 68.0 | 110.0 | 16.0 | 61916            | S61916    | 61916-02     | -         | 61916-2RS    | S61916-2RS |

| * Load Rating (only ISO C98) |            | * Limiting Speed x1000 (rpm) |     | Standard cage type (Others on request) | Weight (kg approx.) |
|------------------------------|------------|------------------------------|-----|----------------------------------------|---------------------|
| C, dyn. N                    | C, stat. N | Grease                       | Oil |                                        |                     |
| 25000                        | 24000      | 5.7                          | 6.8 | J                                      | 304 g               |



**Rodamiento de bolas S61916-2RS-ZEN**

| Caractéristique            | Valeur                                           |
|----------------------------|--------------------------------------------------|
| d - Diámetro interior (mm) | 80                                               |
| D - Diámetro exterior (mm) | 110                                              |
| C - Espesor (mm)           | 16                                               |
| Marca                      | ZEN                                              |
| Tipo del rodamiento        | De bolas                                         |
| Juego                      | Estándar                                         |
| Tipo de sellado            | Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE) |
| Tipo de jaula              | Acero                                            |
| Especificaciones           | Acero inoxidable                                 |
| Rodamiento serie           | 61900 - 6900                                     |
| Unidad de venta            | pieza                                            |

