

Rodamiento magneto BO15-NSK

BO15-NSK

LE BON ROULEMENT

The image contains two technical drawings of the BO15-NSK bearing. The left drawing is a side view showing dimensions: T (total height), C (width), r (fillet radius), r_1 (inner ring fillet radius), B (width of the bearing), and ϕd (inner diameter). The right drawing is a cross-sectional view showing dimensions: r_a (outer ring fillet radius), r_1 (inner ring fillet radius), ϕD_a (outer diameter), and ϕd_a (inner diameter).

Dimensions (mm)					Capacité de Charge (N)				Vitesses limites (tr/min)		Séries Rodamientos	
d	D	E, C, T	r mm	r_1 mm	C_0	C_0	C_0	C_0	Grasse	Huile	Séries E	Séries EH
15	40	10	0.6	0.3	7 400	1 500	768	93	17 000	20 000	BO 15	—

Dimensions Cotes de Montage (mm)			Masse (kg)
d_a mm	D_a mm	r_a mm	kg
19	38	0.6	0.035



Rodamiento magneto BO15-NSK

Caractéristique	Valeur
d - Diámetro interior (mm)	15
D - Diámetro exterior (mm)	40
C - Espesor (mm)	10
Marca	NSK
Tipo del rodamiento	De bolas
Tipo de sellado	No estanco
Rodamiento serie	Magneto
Unidad de venta	pieza

