

# Rodamiento de bolas QJ220-N2-MPA-C3-FAG

## QJ220-N2-MPA-C3-FAG

**LE BON ROULEMENT**

<b>d</b>	100 mm
<b>D</b>	160 mm
<b>B</b>	34 mm
	45 ° Groove angle
<b>a</b>	98 mm
<b>r<sub>n</sub></b>	10,1 mm
<b>t<sub>n</sub></b>	8,5 mm
<b>D<sub>1</sub></b>	153,6 mm
<b>D<sub>2,max</sub></b>	168 mm
<b>d<sub>1</sub></b>	127,7 mm
<b>d<sub>2,ext</sub></b>	112 mm
<b>f<sub>2,max</sub></b>	2,1 mm
<b>f<sub>2,min</sub></b>	2,1 mm
<b>f<sub>3</sub></b>	2 mm
<b>α</b>	35 ° Contact angle
<b>m</b>	4,02 kg Mass
<b>C<sub>r</sub></b>	224000 N Basic dynamic load rating, radial
<b>C<sub>0r</sub></b>	241000 N Basic static load rating, radial
<b>n<sub>0</sub></b>	6600 1/min Limiting speed
<b>n<sub>0</sub></b>	3550 1/min Reference speed
<b>C<sub>10r</sub></b>	11200 N Fatigue limit load, radial



**Rodamiento de bolas QJ220-N2-MPA-C3-FAG**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	100
D - Diámetro exterior (mm)	180
C - Espesor (mm)	34
Marca	FAG
Tipo del rodamiento	De bolas
Juego	Alta velocidad (C3, J30)
Tipo de sellado	No estanco
Tipo de jaula	Macisa latón
Especificaciones	Con dos ranuras de fijación
Rodamiento serie	QJ200
Unidad de venta	pieza

