


Manguito de fijación H2330

H2330





| Dimensions<br>Dimensions |           |            |            |            |           | Poids Net<br>Weight (N) | Matière<br>Material<br>Aluminum alloy<br>6061-T6 | Type<br>Designation              |                                     |                                     |
|--------------------------|-----------|------------|------------|------------|-----------|-------------------------|--------------------------------------------------|----------------------------------|-------------------------------------|-------------------------------------|
| d1<br>(mm)               | d<br>(mm) | d3<br>(mm) | B1<br>(mm) | B2<br>(mm) | G<br>(mm) |                         |                                                  | Norme de<br>sécurité<br>Lock nut | Dispositif<br>de sécurité<br>Washer | Étanchéité<br>Hydraulic<br>Lock nut |
| 100                      | 150       | 180        | 130        | 20         | M 150x2   | 6.4                     | H 2330                                           | M 30                             | M 30                                | M 30 x 1                            |



**Manguito de fijación H2330**

| Caractéristique       | Valeur                |
|-----------------------|-----------------------|
| Longitud (mm)         | 139                   |
| dA - Diámetro del eje | 135                   |
| Marca                 | Genérica alta calidad |
| Diámetro sobre tuerca | 195                   |
| Unidad de venta       | pieza                 |

