

Rodamiento de agujas NAO30X47X16

NAO30X47X16

**LE BON
ROULEMENT**

NAO

NAO.ZW

Designation Designation	Type Type	Weight (g) Poids (g)	Dimensions (mm) Dimensions (mm)					Coefficients de charge (N) Load ratings (N)		Vitesse limite Limiting speed
			d	D	B	F	E	Dynamique C Dynamic C	Statique C ₀ Static C ₀	Unité Unit
30	NAO 30x45x13	71	30	45	13	35	42	15 300	26 600	12 000
	NAO 30x45x17	100	30	45	17	35	48	19 700	30 600	12 300
	NAO 30x45x18 - ZW	110	30	45	18	35	48	20 100	31 200	12 300
	NAO 30x47x16	89.8	30	47	16	35	42	21 100	33 600	12 300
	NAO 30x47x18	108	30	47	18	35	42	25 100	40 600	12 300
	NAO 30x52x18	172	30	52	18	37	48	26 800	43 225	11 000



Rodamiento de agujas NAO30X47X16

Caractéristique	Valeur
d - Diámetro interior (mm)	30
D - Diámetro exterior (mm)	47
C - Espesor (mm)	16
Marca	Genérica alta calidad
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Rodamiento serie	NAO
Unidad de venta	pieza

