

Rodamiento de agujas RNAO35X47X16

RNAO35X47X16

LE BON ROULEMENT

Diamètre utile (mm) Shoulder diameter (mm)	Type Designation	Poids (g) Weight (g)	Dimensions (mm) Dimensions (mm)				Coefficients de charge (N) Basic load ratings (N)			Vitesse limite Limiting Speed
			Fe	D	C	E	Dynamique C _d Dynamic C	Statique C _s Static C	Unité Oil	
35	RNAO 35x45x13	50	35	45	13	42	15 400	20 600	11 400	
	RNAO 35x45x17	60	35	45	17	40	19 700	30 600	11 400	
	RNAO 35x45x26 - ZW	88	35	45	26	40	26 100	53 200	11 400	
	RNAO 35x47x16	75	35	47	16	42	23 100	33 600	11 400	
	RNAO 35x47x18	86	35	47	18	42	26 100	40 850	11 400	
	RNAO 35x47x32 - ZW	140	35	47	32	42	39 900	71 250	11 400	



Rodamiento de agujas RNAO35X47X16

Caractéristique	Valeur
d - Diámetro interior (mm)	35
D - Diámetro exterior (mm)	47
C - Espesor (mm)	16
Marca	Genérica alta calidad
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Rodamiento serie	RNAO
Unidad de venta	pieza

