

# Rodamiento de bolas 3304-A-2RS1-MT33-SKF

3304-A-2RS1-MT33-SKF

**LE BON ROULEMENT**

Principal dimensions		Basic load ratings		Fatigue load limit	Limiting speed	Mass	Designations
d	B	C	C <sub>0</sub>	F <sub>0</sub>	Bearing with shields	kg	Bearing with shields
mm		kN	kN	kN	r/min		
20	52	22.2	23.8	14.8	0.62	33 000	4 000
						0.22	* 3304-A-2Z * 3304-A-2RS1

  

Dimensions					Abutment and fillet dimensions			
d	d <sub>0</sub>	D <sub>0</sub>	r <sub>0,1</sub> max.	r	d <sub>0</sub> min.	d <sub>0</sub> max.	D <sub>0</sub> max.	r <sub>0</sub> max.
mm					mm			
20	29.8	44	1.2	30	27	28.5	45	1



**Rodamiento de bolas 3304-A-2RS1-MT33-SKF**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	20
D - Diámetro exterior (mm)	52
C - Espesor (mm)	22,2
Marca	SKF
Tipo del rodamiento	De bolas
Juego	Estándar
Tipo de sellado	Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE)
Tipo de jaula	Acero
Rodamiento serie	3300
Unidad de venta	pieza

