

# Rodamiento oscilante dos hileras de rodillos 23124-CA-K-C3-W33

23124-CA-K-C3-W33

**LE BON ROULEMENT**

**Alésage conique / Tapered bore**

Dimensions (mm) Dimension (mm)				Coefficient de charge (C3) Load rating (kN)		Vitesse linéaire (1/min) Speed limit (Rpm)		Poids (kg) Weight (lb)	Sigle Designation	
d	D	B	K	Dynamique Dynamic C <sub>3</sub>	Statique Static C <sub>3</sub>	Lubrification Lubrication			Alésage cylindrique Cylindrical bore	Alésage conique Tapered bore
						Grasse Grease	Huile Oil			
120	308	62	4.5	500	681	2001	3060	8	23124	23124 K



**Rodamiento oscilante dos hileras de rodillos 23124-CA-K-C3-W33**

Caractéristique	Valeur
d - Diámetro interior (mm)	120
D - Diámetro exterior (mm)	200
C - Espesor (mm)	62
Marca	Genérica alta calidad
Tipo del rodamiento	Con rodillos oscilantes
Juego	Alta velocidad (C3, J30)
Tipo de sellado	No estanco
Tipo de jaula	Macisa latón
Agujero	Cónico/a
Rodamiento serie	23100
Unidad de venta	pieza

