

# Rodamiento oscilante dos hileras de rodillos 24040-MB-W33

24040-MB-W33

**LE BON ROULEMENT**

**Alésage cylindrique**  
Cylindrical bore

Dimensions (mm) Dimension (mm)				Coefficient de charge (C) Load rating (kN)		Vitesse limite (1/min) Speed limit (Rpm)		Poids (kg) Weight (kg)	Sigle Designation	
d (mm)	D (mm)	B (mm)	r (mm)	Dynamique C <sub>d</sub>	Statique C <sub>s</sub>	Lubrification Lubrication	Alésage cylindrique Cylindrical bore		Alésage conique Tapered bore	
						Grasse Grease		Huile Oil		
200	312	100	0	1204	2076	1423.5	1710	31	24040	24040 K30



**Rodamiento oscilante dos hileras de rodillos 24040-MB-W33**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	200
D - Diámetro exterior (mm)	310
C - Espesor (mm)	109
Marca	Genérica alta calidad
Tipo del rodamiento	Con rodillos oscilantes
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Macisa latón
Agujero	Cilíndrico/a
Rodamiento serie	24000
Unidad de venta	pieza

