

Rodamiento oscilante dos hileras de rodillos 21310-E-C3-SKF

21310-E-C3-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations
d	D	B	C	C_0	Reference speed	Limiting speed	Bearing with cylindrical bore
mm	mm	mm	kN	kN	r/min	kg	-
50	110	27	156	166	38,6	5,600	7,600 3,35 * 21310 E

Dimensions						Abutment and fillet dimensions			Calculation factors			
d	d_2	D_3	b	K	$r_{1,2}$	d_a	D_a	r_a	α	Y_1	Y_2	Y_0
mm	mm	mm	mm	mm	mm	mm	mm	mm	°	-	-	-
50	72,7	96,8	4	3	2	61	99	2	0,24	2,8	4,2	2,8



Rodamiento oscilante dos hileras de rodillos 21310-E-C3-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	50
D - Diámetro exterior (mm)	110
C - Espesor (mm)	27
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Alta velocidad (C3, J30)
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cilíndrico/a
Rodamiento serie	21300
Unidad de venta	pieza

