

Rodamiento oscilante dos hileras de rodillos 22206-EK-SKF

22206-EK-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations
d	D	B	C	C_0	Reference speed	Limiting speed	Bearing with cylindrical bore
mm			kN	kN	r/min	kg	-
30	62	20	64	60	4.4	10 000 14 000 0.29	* 22206 E

Dimensions		Abutment and fillet dimensions			Calculation factors							
d	d_2	D_3	b	K	$r_{1,2}$	d_a min.	D_a max.	r_a max.	α	Y_1	Y_2	Y_0
mm					mm	mm	mm	mm	-			
30	37.6	53	1.7	2	1	35.6	56.4	1	0.31	2.2	3.3	2.2



Rodamiento oscilante dos hileras de rodillos 22206-EK-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	30
D - Diámetro exterior (mm)	62
C - Espesor (mm)	20
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cónico/a
Rodamiento serie	22200
Unidad de venta	pieza

