

# Rodamiento oscilante dos hileras de rodillos 22214-EK-SKF

22214-EK-SKF

**LE BON ROULEMENT**

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations			
d	D	B	C	$C_0$	Reference speed	Limiting speed	Bearing with cylindrical bore tapered bore			
mm			kN	kN	r/min	kg	-			
70	125	31	208	228	25,5	5 000	6 700	3,55	* 22214 E	* 22214 EK

  

Dimensions				Abutment and fillet dimensions			Calculation factors					
d	$d_2$	$D_3$	b	K	$r_{1,2}$	$d_a$ min.	$D_a$ max.	$r_a$ max.	$\alpha$	$Y_1$	$Y_2$	$Y_0$
mm					mm	mm			-			
70	83	110	4	3	1,5	79	116	1,5	0,23	2,9	4,4	2,8



**Rodamiento oscilante dos hileras de rodillos 22214-EK-SKF**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	70
D - Diámetro exterior (mm)	125
C - Espesor (mm)	31
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cónico/a
Rodamiento serie	22200
Unidad de venta	pieza

