

Rodamiento oscilante dos hileras de rodillos 22215-EK-SKF

22215-EK-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations
d	D	B	C	C_0	Reference speed	Limiting speed	Bearing with cylindrical bore
mm			kN	kN	r/min	kg	-
75	130	31	212	240	26.5	4.800	6.300 3,7 * 22215 E
							* 22215 EK tapered bore

Dimensions				Abutment and fillet dimensions			Calculation factors					
d	d_2	D_3	b	K	$r_{1,2}$	d_a min.	D_a max.	r_a max.	α	Y_1	Y_2	Y_0
mm					mm	mm			-			
75	87,8	115	6	3	1,5	84	121	1,5	0,22	3	4,6	2,8



Rodamiento oscilante dos hileras de rodillos 22215-EK-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	75
D - Diámetro exterior (mm)	130
C - Espesor (mm)	31
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cónico/a
Rodamiento serie	22200
Unidad de venta	pieza

