

Rodamiento oscilante dos hileras de rodillos 22312-EK-VA405-SKF

22312-EK-VA405-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load	Speed ratings	Mass	Designations	
d	D	B	C	C_0	P_0	kg	Bearing with cylindrical bore tapered bore	
mm	mm	mm	mm	kN	rpm	kg		
40	130	44	210	335	36.5	1.000	2.1	22312 EK/VA405

Dimensions				Abutment and fillet dimensions				Calculation factors				Permissible accelerations		
d	d_2	D_1	b	K	$r_{1,2}$	d_a	D_a	r_{fa}	r_{fb}	ϵ	Y_1	Y_2	Y_3	For all lubricants rotational times
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm					m/s^2
40	77.9	110	4.3	4.5	2.1	72	138	2	0.25	1.9	2.8	1.8		70.0



Rodamiento oscilante dos hileras de rodillos 22312-EK-VA405-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	60
D - Diámetro exterior (mm)	130
C - Espesor (mm)	46
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cónico/a
Especificaciones	Para aplicacion vibrante
Rodamiento serie	22300
Unidad de venta	pieza

