

Rodamiento oscilante dos hileras de rodillos 22209-E-C4-SKF

22209-E-C4-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations
d	D	B	C	C_0	Reference speed	Limiting speed	Bearing with cylindrical bore
mm			kN	kN	r/min	kg	-
45	85	23	102	88	10,8	7 500	10 000 0,58
							* 22209 E
							* 22209 EK

Dimensions				Abutment and fillet dimensions			Calculation factors					
d	d_2	D_3	b	K	$r_{1,2}$	d_a	D_a	r_a	α	Y_1	Y_2	Y_0
mm					mm	mm	mm	mm	°			
45	54,4	74,4	5,5	3	3,1	52	78	1	0,26	2,6	3,9	2,5



Rodamiento oscilante dos hileras de rodillos 22209-E-C4-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	45
D - Diámetro exterior (mm)	85
C - Espesor (mm)	23
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Muy alta velocidad (C4)
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cilíndrico/a
Rodamiento serie	22200
Unidad de venta	pieza

