

# Rodamiento oscilante dos hileras de rodillos 22313-E-SKF

22313-E-SKF

**LE BON ROULEMENT**

Principal dimensions	Basic load ratings	Fatigue load limit	Speed ratings	Mass	Designations						
d	D	B	$C$	$C_0$	$P_u$	Ref-ence speed	Lim-iting speed	kg	-	Bearing with cylindrical bore	tapered bore
65	340	48	340	360	38	3 000	5 000	3,75	-	* 22313 E	* 22313 EK

  

Dimensions				Abutment and fillet dimensions			Calculation factors					
d	$d_2$	$D_1$	b	K	$r_{1,2}$ min.	$d_a$ min.	$D_a$ max.	$r_a$ max.	$\alpha$	$Y_1$	$Y_2$	$Y_0$
65	81,6	118	8,3	4,5	2,1	77	128	2	0,35	3,9	2,9	1,8



**Rodamiento oscilante dos hileras de rodillos 22313-E-SKF**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	65
D - Diámetro exterior (mm)	140
C - Espesor (mm)	48
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cilíndrico/a
Rodamiento serie	22300
Unidad de venta	pieza

