

Rodamiento oscilante dos hileras de rodillos 22315-E-SKF

22315-E-SKF

LE BON ROULEMENT

Principal dimensions	Basic load ratings	Fatigue load limit	Speed ratings	Mass	Designations						
d	D	B	r_a	r_s	r_1	r_2	d_2	b	K	Bearing with cylindrical bore	tapered bore
mm	kN	kN	r/min	kg	-	-	-	-	-	22315 E	22315 EK
75	160	55	440	475	4.8	3 200	4 300	5,55	-	22315 E	22315 EK

Dimensions					Abutment and fillet dimensions			Calculation factors				
d	d_2	D_1	b	K	$r_{1,2}$ min.	d_a min.	D_a max.	r_a max.	α	Y_1	Y_2	Y_0
mm	-	-	-	-	mm	mm	mm	mm	-	-	-	-
75	92,8	135	8,3	4,5	2,1	87	148	2	0,25	1,9	2,9	1,8



Rodamiento oscilante dos hileras de rodillos 22315-E-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	75
D - Diámetro exterior (mm)	160
C - Espesor (mm)	55
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cilíndrico/a
Rodamiento serie	22300
Unidad de venta	pieza

