

Rodamiento oscilante dos hileras de rodillos 22316-E-SKF

22316-E-SKF

LE BON ROULEMENT

Principal dimensions	Basic load ratings	Fatigue load limit	Speed ratings	Mass	Designations					
d	D	B	C_0	C	P_0	Ref- er- ence speed	Lim- ing speed	kg	Bearing with cylindrical bore	tapered bore
mm	kN	kN	r/min						* 22316 E	* 22316 EK
90	170	58	490	540	54	3 000	4 000	6.6		

Dimensions		Abutment and fillet dimensions				Calculation factors						
d	d ₂	D ₁	b	K	r _{1,2}	d _a min.	D _a max.	r _a max.	e	Y ₁	Y ₂	Y ₀
mm					mm	mm	mm	mm				
90	90.3	143	8.3	4.5	2.1	92	158	2	0.25	1.9	2.9	1.8



Rodamiento oscilante dos hileras de rodillos 22316-E-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	80
D - Diámetro exterior (mm)	170
C - Espesor (mm)	58
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cilíndrico/a
Rodamiento serie	22300
Unidad de venta	pieza

