



22317-E-JA-VA405-SKF



| Principal dimensions |     |    | Basic load ratings | Fatigue load limit         | Speed ratings                  | Mass  | Designations                     |                     |
|----------------------|-----|----|--------------------|----------------------------|--------------------------------|-------|----------------------------------|---------------------|
| d                    | D   | B  | (dynamic)<br>C     | (static)<br>C <sub>0</sub> | Ref.-<br>limb-<br>ing<br>speed | kg    | Bearing with<br>cylindrical hole | tapered hole        |
| mm                   |     |    |                    |                            | mm<br>revs                     | kg    | -                                | -                   |
| 60                   | 100 | 40 | 5200               | 4750                       | 3000                           | 3.000 | • 22047 C 60/100                 | • 22047 C 60/100 AG |

| Dimensions |       |       |     |     |                   | Adjustment and fillet dimensions |               |               | Calculation factors |       |       |       | Permissible accelerations for all lubrications rotational lines |
|------------|-------|-------|-----|-----|-------------------|----------------------------------|---------------|---------------|---------------------|-------|-------|-------|-----------------------------------------------------------------|
| $d$        | $d_1$ | $D_1$ | $b$ | $K$ | $r_{1,2}$<br>(mm) | $d_a$<br>(mm)                    | $D_a$<br>(mm) | $r_a$<br>(mm) | $\alpha$            | $V_1$ | $V_2$ | $V_3$ |                                                                 |
| ax         | 55.6  | 127.3 | 4.5 | 1.2 | 3                 | 0.5                              | 144.8         | 0.6           | 0.55                | 3     | 3     | 3     | $10^3 \text{ s}^{-2}$                                           |



**Rodamiento oscilante dos hileras de rodillos 22317-E-JA-  
VA405-SKF**

| Caractéristique            | Valeur                   |
|----------------------------|--------------------------|
| d - Diámetro interior (mm) | 85                       |
| D - Diámetro exterior (mm) | 180                      |
| C - Espesor (mm)           | 60                       |
| Marca                      | SKF                      |
| Tipo del rodamiento        | Con rodillos oscilantes  |
| Juego                      | Estándar                 |
| Tipo de sellado            | No estanco               |
| Tipo de jaula              | Acero                    |
| Agujero                    | Cilíndrico/a             |
| Especificaciones           | Para aplicacion vibrante |
| Rodamiento serie           | 22300                    |
| Unidad de venta            | pieza                    |

