

Rodamiento oscilante dos hileras de rodillos 22334-CC-C3-W33-SKF

22334-CC-C3-W33-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations			
d	D	B	C	C ₀	Reference speed	Limiting speed	Bearing with cylindrical bore			
mm			kN	kN	r/min	kg				
170	360	120	1 760	2 560	375	1 400	1 800	61	* 22334 CC/W33	* 22334 CCK/W33

Dimensions				Abutment and fillet dimensions			Calculation factors					
d	d ₂	D ₂	b	K	r _{1,2}	d _a	D _a	r _a	e	Y ₁	Y ₂	Y ₃
mm					mm	mm	mm	mm				
170	213	300	16,7	9	4	187	343	3	0,33	2	3	2



**Rodamiento oscilante dos hileras de rodillos 22334-CC-
C3-W33-SKF**

Caractéristique	Valeur
d - Diámetro interior (mm)	170
D - Diámetro exterior (mm)	360
C - Espesor (mm)	120
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Alta velocidad (C3, J30)
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cilíndrico/a
Rodamiento serie	22300
Unidad de venta	pieza

