

# Rodamiento oscilante dos hileras de rodillos 23072-CC-K-W33-SKF

23072-CC-K-W33-SKF

**LE BON ROULEMENT**

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations			
d	D	B	C	$C_0$	Reference speed	Limiting speed	Bearing with cylindrical bore			
mm			kN	kN	r/min	kg	-			
260	540	124	2 750	4 800	345	950	1 200	110	* 23072 CC/W33	* 23072 CCK/W33

  

Dimensions					Abutment and fillet dimensions			Calculation factors				
d	$d_2$	$D_3$	b	K	$r_{1,2}$	$d_a$	$D_a$	$r_a$	$\epsilon$	$Y_1$	$Y_2$	$Y_3$
mm					mm	mm	mm	mm	-			
260	404	483	22,3	12	5	378	522	4	0,23	2,9	4,4	2,8



**Rodamiento oscilante dos hileras de rodillos 23072-CC-K-  
W33-SKF**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	360
D - Diámetro exterior (mm)	540
C - Espesor (mm)	134
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cónico/a
Rodamiento serie	23000
Unidad de venta	pieza

