

# Rodamiento oscilante dos hileras de rodillos 23220-CC-K-W33-SKF

23220-CC-K-W33-SKF

**LE BON ROULEMENT**

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations
d	D	B	C	$C_0$	Reference speed	Limiting speed	Bearing with cylindrical bore
mm			kN	kN	r/min	kg	
100	180	60,3	475	600	63	2 400	3 400
						6,85	* 23220 CC/W33
							* 23220 CCK/W33

  

Dimensions		Abutment and fillet dimensions			Calculation factors							
d	$d_2$	$D_3$	b	K	$r_{1,2}$	$d_a$	$D_a$	$r_a$	$\epsilon$	$Y_1$	$Y_2$	$Y_3$
mm					mm	mm	mm	mm				
100	117	153	8,3	4,5	2,5	112	168	2	0,33	2	3	2



**Rodamiento oscilante dos hileras de rodillos 23220-CC-K-  
W33-SKF**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	100
D - Diámetro exterior (mm)	180
C - Espesor (mm)	63,3
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cónico/a
Rodamiento serie	23200
Unidad de venta	pieza

