

Rodamiento oscilante dos hileras de rodillos 23228-CC-K-W33-SKF

23228-CC-K-W33-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations
d	D	B	C	C_0	Reference speed	Limiting speed	Bearing with cylindrical bore
mm			kN	kN	r/min	kg	
140	290	88	915	1250	320	1700	2400
							39
							* 23228 CC/W33
							* 23228 CCK/W33

Dimensions		Abutment and fillet dimensions			Calculation factors							
d	d_2	D_3	b	K	$r_{1,2}$	d_a	D_a	r_a	ϵ	Y_1	Y_2	Y_3
mm					mm	mm	mm	mm				
140	165	232	31.3	6	3	154	236	2.5	0.33	2	3	2



**Rodamiento oscilante dos hileras de rodillos 23228-CC-K-
W33-SKF**

Caractéristique	Valeur
d - Diámetro interior (mm)	140
D - Diámetro exterior (mm)	250
C - Espesor (mm)	88
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cónico/a
Rodamiento serie	23200
Unidad de venta	pieza

