

Rodamiento oscilante dos hileras de rodillos 23220-CC-W33-C3-SKF

23220-CC-W33-C3-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations
d	D	B	C	C_0	Reference speed	Limiting speed	Bearing with cylindrical bore
mm			kN		kW	r/min	kg
100	180	60,3	475	600	63	2 400	3 400
						6,85	* 23220 CC/W33
							* 23220 CCK/W33

Dimensions		Abutment and fillet dimensions			Calculation factors							
d	d_2	D_3	b	K	$r_{1,2}$	d_a	D_a	r_a	ϵ	Y_1	Y_2	Y_3
mm					min.	min.	max.	max.				
100	117	153	8,3	4,5	2,5	112	168	2	0,33	2	3	2



**Rodamiento oscilante dos hileras de rodillos 23220-CC-
W33-C3-SKF**

Caractéristique	Valeur
d - Diámetro interior (mm)	100
D - Diámetro exterior (mm)	180
C - Espesor (mm)	63,3
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Alta velocidad (C3, J30)
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cilíndrico/a
Rodamiento serie	23200
Unidad de venta	pieza

