

# Rodamiento oscilante dos hileras de rodillos 23248-CC-W33-C3-SKF

23248-CC-W33-C3-SKF

**LE BON ROULEMENT**

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations			
d	D	B	C	$C_0$	Reference speed	Limiting speed	Bearing with cylindrical bore			
mm			kN	kN	r/min	kg				
240	440	360	2 900	4 300	345	950	1 300	130	* 23248 CC/W33	* 23248 CCK/W33

  

Dimensions		Abutment and fillet dimensions			Calculation factors							
d	$d_2$	$D_2$	b	K	$r_{1,2}$	$d_a$	$D_a$	$r_a$	$\epsilon$	$Y_1$	$Y_2$	$Y_3$
mm					mm	mm	mm	mm				
240	286	374	22,3	12	4	257	423	3	0,35	1,9	2,9	1,8



**Rodamiento oscilante dos hileras de rodillos 23248-CC-  
W33-C3-SKF**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	240
D - Diámetro exterior (mm)	440
C - Espesor (mm)	160
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Alta velocidad (C3, J30)
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cilíndrico/a
Rodamiento serie	23200
Unidad de venta	pieza

