



30312-J2/Q-SKF



Principal dimensions			Basic load ratings		Fatigue load limit		Speed ratings		Mass		Designation		Dimension series to ISO 355 (ABMA)	
d	D	T	C_0	C_1	P_0	Relative speed	Limiting speed	m_1	m_2					
mm			kN	kN	kN	min	mm/s	kg						
60	130	32.5	148	194	23.6	4 000	5 300	1.81		30322 J2/Q		378		

Dimensions				Abutment and fillet dimensions										Calculation factors				
d	d_1	D	C	r_{D1} (mm)	r_{D2} (mm)	ρ	R_1 (mm)	R_2 (mm)	R_3 (mm)	R_4 (mm)	R_5 (mm)	C_1 (mm)	C_2 (mm)	T_1 (mm)	T_2 (mm)	α	γ	γ_0
mm																		
60	91.8	51	24	3	2.5	26	77	72	122	118	120	5	7.5	3	2.5	0.35	1.7	0.3



Rodamiento de rodillos cónicos 30312-J2/Q-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	60
D - Diámetro exterior (mm)	130
C - Espesor (mm)	33,5
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	31
Espesor de la cubeta	26
Rodamiento serie	30300
Unidad de venta	pieza

