

Rodamiento de rodillos cónicos 31305-J2-SKF

31305-J2-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings	Fatigue load limit	Speed ratings	Mass	Designation	Dimension series to ISO 155 (ABMA)			
d	D	T	C_0	C_1	$P_{0.2}$	Ref. limit speed	kg			
mm	mm	mm	kN	kN	r/min					
25	62	18,25	38	40	4,4	7500	11 000	0,27	31305 J2	770

Dimensions		Mounting and fillet dimensions										Calculation factors						
d	d ₁	B	C	$r_{1,2}$	$r_{3,4}$	a	e_1	e_2	D_1	D_2	D_3	C_1	C_2	T_1	T_2	α	γ	γ_0
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
25	43,8	17	13	1,5	1,5	20	34	32	47	55	59	2	5	1,5	1,5	0,83	0,72	0,4



Rodamiento de rodillos cónicos 31305-J2-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	25
D - Diámetro exterior (mm)	62
C - Espesor (mm)	18,25
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	17
Espesor de la cubeta	13
Rodamiento serie	31300
Unidad de venta	pieza

