



32210-J2/Q-SKF



Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designation	Dimension series to ISO 355 (ABMA)
d	D	T	C_0	C_1	P_0	Revolutions per minute	Limiting speed	kg	—	—
mm	mm	mm	kN	kN	kN	r/min	m/min	kg	—	—
50	90	34,75	32,5	100	11,4	5 600	7 000	0,43	32220 J2/0	32C

Dimensions			Abutment and fillet dimensions														Calculation factors		
d	d_1	D	C	r_{D1} mm	r_{D2} mm	r	d_6 mm	d_7 mm	D_8 mm	D_9 mm	D_{10} mm	C_{10} mm	T_2 mm	T_3 mm	α	γ	γ_0		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	°	°	°		
50	18,6	23	19	1,5	1,5	21	58	57	76	83	85	3	5,5	1,5	1,5	—	0,0		



Rodamiento de rodillos cónicos 32210-J2/Q-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	50
D - Diámetro exterior (mm)	90
C - Espesor (mm)	24,75
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	23
Espesor de la cubeta	19
Rodamiento serie	32200
Unidad de venta	pieza

