



33010/Q-SKF



Principal dimensions			Basic load ratings		Fatigue load limits		Speed ratings		Mass	Designation	Dimension series to ISO 3306 (ABMA)
<i>d</i>	<i>D</i>	<i>T</i>	<i>C</i> ₁₀	<i>C</i> ₉₀	<i>P</i> ₀	<i>P</i> ₁	Refr. speed	Limit speed			
mm	mm	mm	kN	kN	kN	kN	r/min	r/min	kg	—	—
50	80	24	69.3	202	11.4	6 000	8 000	0.45	3306/D		20C

Dimensions			Abutment and fillet dimensions													Calculation factors				
<i>d</i>	<i>d</i> ₁	<i>D</i>	<i>C</i>	<i>r</i> _{1a} mm	<i>r</i> _{1b} mm	<i>r</i> _{1c} mm	<i>a</i>	<i>d</i> ₂ mm	<i>d</i> ₃ mm	<i>D</i> ₁ mm	<i>D</i> ₂ mm	<i>D</i> ₃ mm	<i>C</i> ₁ mm	<i>C</i> ₂ mm	<i>T</i> ₁ mm	<i>T</i> ₂ mm	<i>a</i>	<i>Y</i>	<i>Y</i> ₉	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm			
50	45.5	24	19	1	1	17	58	56	72	74	75	4	5	1	1	0.33	1.9	1	1	



Rodamiento de rodillos cónicos 33010/Q-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	50
D - Diámetro exterior (mm)	80
C - Espesor (mm)	24
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	24
Espesor de la cubeta	19
Rodamiento serie	33000
Unidad de venta	pieza

