


NU226-ECML-C3-SKF

**LE BON
ROULEMENT**

Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations	Alternative cage	
d	D	B	Dynamic C	Static C ₀	P ₀	Reference speed	Limiting speed	Bearing with standard cage	Alternative standard cage	
mm			kN		kN	1/min	kg	—		
130	230	40	415	455	51	3 200	3 400	6.45	* NU 226 ECP	J, M, HL

Dimensions			Abutment and fillet dimensions										Calculation factor	Angle ring designation	Mass	Dimensions
d	d ₁	D ₁	F, S	r _{1,2}	r _{3,4}	s	d ₂	d ₄	d ₆ , D ₂	D ₄ max.	r ₆	r ₂ max.	f ₀	h ₀	kg	B ₁ B ₂
mm				min.	min.		min.	max.	min.	max.	max.	max.				mm
130	384	202	353.5	3	3	2.1	144	150	157	215	2.5	2.5	0.15	NU 226 EC	0.75	11 27



Rodamiento de rodillos cilíndricos NU226-ECML-C3-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	130
D - Diámetro exterior (mm)	230
C - Espesor (mm)	40
Marca	SKF
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Alta velocidad (C3, J30)
Tipo de jaula	Macisa latón
Rodamiento serie	NU200
Unidad de venta	pieza

