

Rodamiento de rodillos cilíndricos NU2206-ECP-C3-SKF

NU2206-ECP-C3-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations			
d	B	C_d	C_0	P_0	Reference speed	Limiting speed	Bearing with standard cage Alternative standard cage			
mm		kN		kN	min	mm/s	kg			
30	62	20	55	49	0.1	13 000	14 000	0.26	* NU 2206-ECP	J, ML, PH

Dimensions				Abutment and fillet dimensions								Calculation factor	Angle ring	Max. dimension	Dimension
d	d_1	D_2	F.E	$r_{1,2}$ min.	$r_{3,4}$ min.	r_5	r_6 max.	D_5 min.	D_6 max.	r_7 max.	r_8 max.	k_1	Designation	Max. dimension	Dimension
mm				mm		mm		mm		mm				kg	mm
30	-	52.5	37.5	1	0.6	0.8	34.3	36.1	39	55.9	1	0.6	0.2	-	-



Rodamiento de rodillos cilíndricos NU2206-ECP-C3-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	30
D - Diámetro exterior (mm)	62
C - Espesor (mm)	20
Marca	SKF
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Alta velocidad (C3, J30)
Tipo de jaula	Poliamido
Rodamiento serie	NU2200
Unidad de venta	pieza

