

Rodamiento de rodillos cilíndricos NU2315-ECJ-SKF

NU2315-ECJ-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load	Speed ratings	Mass	Designations	Alternative		
d	B	C	C ₀	P ₀	Refer-ence speed	Limiting speed	Bearing with standard cage	Standard cage		
mm		kN	kN	(t/min)	rpm	kg				
75	188	55	380	400	30	4 500	5 500	4,8	* NU2315 BCP	A, ML

Dimensions		Abutment and fillet dimensions										Calculation factor	Angle ring designation	Mass	Dimensions				
d	d ₁	D ₁	F, E	r _{1,2}	r _{3,4}	r ₅	d ₁	d ₂	d ₃	D ₁	r ₁	r ₂	r ₃	r ₄	r ₅	k ₁		M ₁	M ₂
mm				min.	min.		min.	max.	min.	max.	min.	max.	min.	max.	min.			kg	mm
75	304	136	95	2,1	2,1	4,8	87	92	97	148	2	2	0,25	HJ2315 EC	0,62			11	39,5



Rodamiento de rodillos cilíndricos NU2315-ECJ-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	75
D - Diámetro exterior (mm)	160
C - Espesor (mm)	55
Marca	SKF
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Acero
Rodamiento serie	NU2300
Unidad de venta	pieza

