



NU2320-ECJ-C3-SKF



Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designations	
d	D	B	d _{static}	C _{static}	P ₀	Reference speed	Limiting speed	kg	Bearing with standard cage	Alternative standard cage
mm			nN		kN	r/min		kg	—	
200	215	73	670	735	85	3 200	3 800	1.2	* NU 2320 ECP	J, M, ML

Dimensions			Adjustment and fit dimensions							Calculation factor	Angle ring designation	Mass	Dimensions		
d	d ₁	D ₂	F, E	r _{1,2} max.	r _{1,2} min.	d ₂ max.	d ₂ min.	D ₂ max.	D ₂ min.	r ₂ max.	r ₂ min.	—	kg	mm	
200	136	182	1275	3	5.6	134	134	133	133	2.5	2.5	NU 2320 EC	0.91	33	37.5



Rodamiento de rodillos cilíndricos NU2320-ECJ-C3-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	100
D - Diámetro exterior (mm)	215
C - Espesor (mm)	73
Marca	SKF
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Alta velocidad (C3, J30)
Tipo de jaula	Acero
Rodamiento serie	NU2300
Unidad de venta	pieza

