



Rodamiento de bolas a rótula 1205-EKTN9-C3-SKF

1205-EKTN9-C3-SKF



Principal dimensions		Basic load ratings		Fatigue	Speed ratings		Mass	Designations	
d	D	B	C	C ₉₀	P ₀	P _{0.01}	kg	Bearing with	tapered bore
mm						chain			
25	52	15	34,3	4	0,21	28 000	0,14	1205 EKN9	1205 EKTN9

Dimensions				Abutment and fillet dimensions			Calculation factors				
d	d ₂	D ₁	r _{1,2} (mm)	R ₁ (mm)	R ₂ (mm)	r ₃ (mm)	k _r	σ	γ ₁	γ ₂	γ ₃
mm				mm							
25	32,2	46,4	1	30,6	44,4	3	0,04	0,38	2,2	3,5	2,5



Rodamiento de bolas a rótula 1205-EKTN9-C3-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	25
D - Diámetro exterior (mm)	52
C - Espesor (mm)	15
Marca	SKF
Tipo del rodamiento	De bolas
Juego	Alta velocidad (C3, J30)
Tipo de sellado	No estanco
Tipo de jaula	Poliamido
Agujero	Cónico/a
Rodamiento serie	1200
Unidad de venta	pieza

