



# Rodamiento de bolas a rótula 1207-EKTN9-SKF

## 1207-EKTN9-SKF


**LE BON  
ROULEMENT**


| Principal dimensions |    |    | Basic load ratings |                 | Fatigue load limit | Speed ratings   |                | Mass | Designations                               |  |  |
|----------------------|----|----|--------------------|-----------------|--------------------|-----------------|----------------|------|--------------------------------------------|--|--|
| d                    | D  | B  | C                  | C <sub>90</sub> | P <sub>0</sub>     | Reference speed | Limiting speed | kg   | Bearing with cylindrical bore tapered bore |  |  |
| mm                   |    |    |                    |                 |                    | min             | min            |      |                                            |  |  |
| 96                   | 72 | 17 | 39                 | 6               | 0,34               | 25 000          | 53 000         | 0,32 | 1207 EKTN9 1287 GKTN9                      |  |  |

| Dimensions |                |                |                       | Abutment and fillet dimensions |                     |                     | Calculation factors |      |                |                |                |
|------------|----------------|----------------|-----------------------|--------------------------------|---------------------|---------------------|---------------------|------|----------------|----------------|----------------|
| d          | d <sub>2</sub> | D <sub>1</sub> | r <sub>1,2</sub> min. | R <sub>a</sub> max.            | D <sub>a</sub> max. | r <sub>a</sub> max. | f <sub>0</sub>      | e    | Y <sub>1</sub> | Y <sub>2</sub> | Y <sub>3</sub> |
| mm         |                |                |                       | mm                             |                     |                     |                     |      |                |                |                |
| 96         | 47             | 60,3           | 1,3                   | 42                             | 66                  | 3,1                 | 0,04                | 0,29 | 2,7            | 4,2            | 2,8            |



**Rodamiento de bolas a rótula 1207-EKTN9-SKF**

| Caractéristique            | Valeur     |
|----------------------------|------------|
| d - Diámetro interior (mm) | 35         |
| D - Diámetro exterior (mm) | 72         |
| C - Espesor (mm)           | 17         |
| Marca                      | SKF        |
| Tipo del rodamiento        | De bolas   |
| Juego                      | Estándar   |
| Tipo de sellado            | No estanco |
| Tipo de jaula              | Poliamido  |
| Agujero                    | Cónico/a   |
| Rodamiento serie           | 1200       |
| Unidad de venta            | pieza      |

