

Rodamiento de bolas a rótula 1307-ETN9-C3-SKF

1307-ETN9-C3-SKF

LE BON ROULEMENT

| Principal dimensions | | Basic load ratings | | Fatigue load limit | Speed ratings | | Mass | Designations | | | |
|----------------------|---|--------------------|----|--------------------|----------------|-----------------|----------------|--------------|-------------------------------|-------------|--------------|
| d | D | B | C | C ₁₀ | P ₀ | Reference speed | Limiting speed | kg | Bearing with cylindrical bore | | tapered bore |
| mm | | | mm | | mm | min | max | | 1307 ETN9 | 1307 0X TN9 | |

| Dimensions | | | | Abutment and fillet dimensions | | | Calculation factors | | | | |
|------------|----------------|----------------|-----------------------|--------------------------------|---------------------|---------------------|---------------------|------|----------------|----------------|----------------|
| d | d ₂ | D ₁ | r _{1,2} min. | r ₁ min. | D ₁ max. | r ₂ max. | k ₁ | e | Y ₁ | Y ₂ | Y ₃ |
| mm | | | | mm | | | | | | | |
| 96 | 51.5 | 69.5 | 1.5 | 44 | 71 | 3.5 | 0.04 | 0.25 | 0.5 | 3.0 | 2.5 |



Rodamiento de bolas a rótula 1307-ETN9-C3-SKF

| Caractéristique | Valeur |
|----------------------------|--------------------------|
| d - Diámetro interior (mm) | 35 |
| D - Diámetro exterior (mm) | 80 |
| C - Espesor (mm) | 21 |
| Marca | SKF |
| Tipo del rodamiento | De bolas |
| Juego | Alta velocidad (C3, J30) |
| Tipo de sellado | No estanco |
| Tipo de jaula | Poliamido |
| Agujero | Cilíndrico/a |
| Rodamiento serie | 1300 |
| Unidad de venta | pieza |

