

Rodamiento de bolas 2206-EK-TN9-SKF

2206-EK-TN9-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designations		
d	D	B	C	C ₀	P ₀	Reference speed	Limiting speed	kg	Bearing with cylindrical bore	tapered bore
mm		mm		mm		rpm				
20	62	20	23,6	6,7	0,25	22000	35000	0,24	2206 EKTN9	2206 DKTN9

Dimensions				Abutment and fillet dimensions			Calculation factors				
d	d ₂	D ₁	r _{1,2} min.	r ₁ min.	D ₂ max.	r ₂ max.	k ₁	σ	γ ₁	γ ₂	γ ₃
mm				mm							
20	38,8	55	1	35,8	56,4	1	0,045	0,33	1,9	3	2



Rodamiento de bolas 2206-EK-TN9-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	30
D - Diámetro exterior (mm)	62
C - Espesor (mm)	20
Marca	SKF
Tipo del rodamiento	De bolas
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Poliamido
Agujero	Cónico/a
Rodamiento serie	2200
Unidad de venta	pieza

