



Rodamiento de bolas 2210-EK-TN9-C3-SKF

2210-EK-TN9-C3-SKF



Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designations		
d	D	B	C	C ₉₀	P ₀	Reference speed	Limiting speed	kg	Bearing with cylindrical bore		tapered bore
mm						min					
50	90	23	33,8	11,2	0,57	34 000	9 500	0,4	2210 EK TN9		2210 GKTW9

Dimensions				Abutment and fillet dimensions			Calculation factors				
d	d ₂	D ₁	r _{1,2} min.	R _a max.	D _a max.	r _a max.	k _r	e	Y ₁	Y ₂	Y ₃
mm				mm							
50	61,5	81,5	1,3	57	83	3,1	0,045	0,29	2,7	4,2	2,8



Rodamiento de bolas 2210-EK-TN9-C3-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	50
D - Diámetro exterior (mm)	90
C - Espesor (mm)	23
Marca	SKF
Tipo del rodamiento	De bolas
Juego	Alta velocidad (C3, J30)
Tipo de sellado	No estanco
Tipo de jaula	Poliamido
Agujero	Cónico/a
Rodamiento serie	2200
Unidad de venta	pieza

