



Rodamiento de bolas 2212-EK-TN9-SKF

2212-EK-TN9-SKF


**LE BON
ROULEMENT**


Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designations		
d	D	B	C	C ₉₀	P ₀	Reference speed	Limiting speed	kg	Bearing with cylindrical bore		tapered bore
mm					kN	min	min				
40	110	28	48,8	37	0,88	11 000	8 000	1,1	2212 ETN9		2212 EKTW9

Dimensions				Abutment and fillet dimensions			Calculation factors				
d	d ₂	D ₁	r _{1,2} min.	R _s min.	D _s max.	r _s max.	k _r	ε	Y ₁	Y ₂	Y ₃
mm				mm							
40	74,6	98,6	1,5	69	101	1,5	0,045	0,24	2,6	4,1	2,8



Rodamiento de bolas 2212-EK-TN9-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	60
D - Diámetro exterior (mm)	110
C - Espesor (mm)	28
Marca	SKF
Tipo del rodamiento	De bolas
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Poliamido
Agujero	Cónico/a
Rodamiento serie	2200
Unidad de venta	pieza

