

Rodamiento de bolas 2201-E-2RS1-TN9-SKF

2201-E-2RS1-TN9-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designations		
d	D	B	C	C ₀	F ₀	Reference speed	Limiting speed	Bearing with cylindrical bore	tapered bore	
mm			mm	mm		rpm		kg	-	
12	32	14	8,52	1,9	0,096	41 000	30 000	0,053	2201 ETN9	-

Dimensions				Abutment and fillet dimensions			Calculation factors				
d	d ₂	D ₁	r _{1,2} min.	R _s min.	D _s max.	r _s max.	k	e	f ₁	f ₂	f ₃
mm				mm							
12	17,5	26,5	0,6	19,2	27,6	0,6	0,045	0,5	1,25	2	3,3



Rodamiento de bolas 2201-E-2RS1-TN9-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	12
D - Diámetro exterior (mm)	32
C - Espesor (mm)	14
Marca	SKF
Tipo del rodamiento	De bolas
Juego	Estándar
Tipo de sellado	Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE)
Tipo de jaula	Poliamido
Agujero	Cilíndrico/a
Rodamiento serie	2200
Unidad de venta	pieza

