



Rodamiento de bolas 2205-E-TN9-C3-SKF

2205-E-TN9-C3-SKF



Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designations	
d	D	B	C	C ₉₀	P ₀	Reference speed	Limiting speed	kg	Bearing with cylindrical bore	tapered bore
mm			mm		mm	min	min			
25	52	18	36,6	4,4	0,22	28 000	58 000	0,35	2205 CTN9	2205 DKTW9

Dimensions				Abutment and fillet dimensions			Calculation factors				
d	d ₂	D ₁	r _{1,2} (mm)	R _a (mm)	D _a (mm)	r _a (mm)	k _r	σ	γ ₁	γ ₂	γ ₃
mm				mm							
25	30,3	46,1	1	30,6	46,4	1	0,045	0,35	1,8	2,8	1,8



Rodamiento de bolas 2205-E-TN9-C3-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	25
D - Diámetro exterior (mm)	52
C - Espesor (mm)	18
Marca	SKF
Tipo del rodamiento	De bolas
Juego	Alta velocidad (C3, J30)
Tipo de sellado	No estanco
Tipo de jaula	Poliamido
Agujero	Cilíndrico/a
Rodamiento serie	2200
Unidad de venta	pieza

