

# Rodamiento de bolas 2206-E-2RS1-TN9-SKF

2206-E-2RS1-TN9-SKF

**LE BON ROULEMENT**

Principal dimensions		Basic load ratings		Fatigue	Speed ratings		Mass	Designations		
d	D	B	C	C <sub>0</sub>	F <sub>0</sub>	Reference speed	Limiting speed	kg	Bearing with cylindrical bore	tapered bore
mm		mm		mm		r/min				
20	62	20	23,6	6,7	0,25	22000	35000	0,24	2206 CTN9	2206 DKTN9

  

Dimensions				Abutment and fillet dimensions			Calculation factors				
d	d <sub>2</sub>	D <sub>1</sub>	r <sub>1,2</sub> (mm)	r <sub>1</sub> (mm)	D <sub>2</sub> (mm)	r <sub>2</sub> (mm)	k	e	f <sub>1</sub>	f <sub>2</sub>	f <sub>3</sub>
mm				mm							
20	38,8	55	1	35,8	56,4	1	0,045	0,33	1,9	3	2



**Rodamiento de bolas 2206-E-2RS1-TN9-SKF**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	30
D - Diámetro exterior (mm)	62
C - Espesor (mm)	20
Marca	SKF
Tipo del rodamiento	De bolas
Juego	Estándar
Tipo de sellado	Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE)
Tipo de jaula	Poliamido
Agujero	Cilíndrico/a
Rodamiento serie	2200
Unidad de venta	pieza

