



Rodamiento de bolas 2207-E-TN9-SKF

2207-E-TN9-SKF



Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designations		
d	D	B	C	C ₉₀	P ₀	Reference speed	Limiting speed	kg	Bearing with cylindrical bore	Tapered bore	
mm					kN	min	min				
35	72	23	35,2	8,8	0,455	38 000	52 000	0,4	2207 ETN9	2207 GKTW9	

Dimensions				Abutment and fillet dimensions			Calculation factors				
d	d ₂	D ₁	r _{1,2} min.	r _a min.	D _a max.	r _a max.	i _r	e	Y ₁	Y ₂	Y ₃
mm				mm							
35	45,5	64,2	1,3	42	65	3,1	0,045	0,33	2	3,1	2,2



Rodamiento de bolas 2207-E-TN9-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	35
D - Diámetro exterior (mm)	72
C - Espesor (mm)	23
Marca	SKF
Tipo del rodamiento	De bolas
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Poliamido
Agujero	Cilíndrico/a
Rodamiento serie	2200
Unidad de venta	pieza

