



Rodamiento de bolas 2207-E-TN9-C3-SKF

2207-E-TN9-C3-SKF



Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designations		
d	D	B	C	C ₉₀	P ₀	Reference speed	Limiting speed	kg	Bearing with cylindrical bore		tapered bore
mm					N	min	min		—		
35	72	23	35,2	8,8	0,455	38 000	52 000	0,4	2207 ETN9		2207 GKTW9

Dimensions				Abutment and fillet dimensions			Calculation factors				
d	d ₂	D ₁	r _{1,2} min.	r _a min.	D _a max.	r _a max.	i _r	e	Y ₁	Y ₂	Y ₃
mm				mm							
35	45,5	64,2	1,3	42	65	3,1	0,045	0,33	2	3,1	2,2



Rodamiento de bolas 2207-E-TN9-C3-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	35
D - Diámetro exterior (mm)	72
C - Espesor (mm)	23
Marca	SKF
Tipo del rodamiento	De bolas
Juego	Alta velocidad (C3, J30)
Tipo de sellado	No estanco
Tipo de jaula	Poliamido
Agujero	Cilíndrico/a
Rodamiento serie	2200
Unidad de venta	pieza

