

Rodamiento de bolas 2216-E-TN9-C3-SKF

2216-E-TN9-C3-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designations		
d	D	B	C	C_0	F_0	Reference speed	Limiting speed	kg	Bearing with cylindrical bore	tapered bore
mm			mm			min	max			
89	140	33	65	25,5	1,25	6 500	4 000	2	2216 ETN9	2216 EKTW9

Dimensions				Abutment and fillet dimensions			Calculation factors				
d	d_1	D_1	$r_{1,2}$ min.	r_1 min.	D_2 max.	r_2 max.	α	ϵ	β_1	β_2	β_3
mm				mm							
89	99	127	2	91	129	2		0,045	0,22	2,9	4,5



Rodamiento de bolas 2216-E-TN9-C3-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	80
D - Diámetro exterior (mm)	140
C - Espesor (mm)	33
Marca	SKF
Tipo del rodamiento	De bolas
Juego	Alta velocidad (C3, J30)
Tipo de sellado	No estanco
Tipo de jaula	Poliamido
Agujero	Cilíndrico/a
Rodamiento serie	2200
Unidad de venta	pieza

